### **30m High Frequency**

## Laser Distance Measuring Module

## **Key Properties**

- Measurement Range: 0.05 ~ 30m
- Measurement Frequency: 90 Hz (Max)
- Measurement Accuracy: ±2cm @ 0~2m ≤1% @ 2~30m
- Wavelength: 780 nm
- Communication Interface: TTL (UART)



## Application

Industrial Manufacturing / Automation Equipment / Automatic Classification Rangefinder / Service Robot Positioning / Industrial & Livestock Stock Inspection Container capacity detection / Security camera triggering / Parking space detection

## **Product Code**

Product	Measure Range	Frequency	Туре	Communication Interface	
LRF: Laser Rang Finder	30M: 30 meter	90: 90Hz	HS: High-Frequency Standard	Default: TTL (UART)	
				Option: USB (converter)	
Example: LRF30M90HS					

### Introduction

High Frequency Laser Distance Measuring Module is suitable for various applications such as UAVs, floor sweepers, industrial robots, and related fields. It is based on the TOF ranging principle and utilizes a 780nm laser. The module is characterized by its small size, low cost, excellent performance, and strong anti-environmental light interference ability, making it a great upgrade alternative product.

With a maximum measurement frequency of 90Hz, it is ideal for measuring dynamic targets and real-time applications. The module's compact design makes it easy to integrate into any system or device. It uses a standard TTL (UART) communication interface, which allows users to develop and program their own applications.





# 1. Specifications

Technical specifications				
Model Name	LRF30M90HS			
Measurement Range	0.05m ~ 30m			
Measurement Frequency	90Hz (Max)			
Magguramant Agguragy	±2cm @ 0~2m			
Measurement Accuracy	≤1% @ 2~30m			
Wavelength	780nm			
Measurement Method	Time-of-Flight			
Anti-ambient Light	100K LUX @ 10m			
Electrical				
Input Voltage	3.3~5V DC			
Power Consumption	80mA@5V			
Communication				
Communication Interface	3.3V TTL UART			
Data Resolution	1 mm			
Baud Rate	115200bps			
Mechanical				
Dimensions	20 x 22 x 14 mm			
Weight	~8g			
Environmental				
Operating Temperature	-10°C~60°C			
Storage Temperature	20°C~70°C			

## 2. Pin Assignment

1	GND		
2	Vcc		
3	RXD		
4	TXD		





### High Frequency Laser Distance Measuring Module

## 3. Communication

### 3.1 UART configuration parameters:

8N1 with default 115200 baud rate, byte data are expressed in ASCII.

Data bits: 8

Parity bits: None

Stop bits: 1

\*The protocol data frame is transmitted in ASCII code and interpreted in hexadecimal.

### 3.2 Communication frame format:

1	2	3	4	5	6	7	8	9	10	11
Head	Address	Command	Reg	ister	Da	ata	CheckSu	ım (CRC)	Ei	nd
'~'	0x00~0xFF	0x00~0xFF	0~6	5535	0~6	5535	0~6	5535	'\r'	'\n'

\*Head fixed as '~' and End fixed as '\r\n' in ASCII type.

\*Example: The serial port receives the string in ASCII code: ~01030100019AC5CD\r\n

\*'~': Data frame starters.

\*01: Address of sensor.

\*03: Command code.

\*0100: Parameter register.

\*019A: Data of measurement result in hexadecimal, 019A is 410mm.

\*C5CD: CheckSum(CRC16)

\*'\r\n': Data frame end.

### 4. Command List

Single Measurement	~01030100000185F6\r\n		
Continuous Measurement	~010600000089CA\r\n		
Stop Measurement	~01060000001480A\r\n		
Laser ON	~0106003000014805\r\n		
Laser OFF	~0106003000089C5\r\n		













